



: 19.09.2016

: 02.05.2015

1 / /

: **635 OXIDE YELLOW**

: 635

General Paint Co. SAL
P.O. Box 7623
Beirut
LEBANON
www.generalpaint.biz

: Product safety department
: During normal opening times: (961) 9 925990 /1/2

2



3 H226



2 H315

3 H336

5 H333

(GHS).



GHS02 GHS07

xylene
Solvent naphtha (petroleum), light arom.
2,3-epoxypropyl neodecanoate



: 19.09.2016

: 02.05.2015

: 635 OXIDE YELLOW

(1)

/ / / / / /

():

().

/ / / / /

PBT ()

vPvB ()

PBT:

vPvB:

3 /

123-86-4	<i>n</i> -butyl acetate	3, H226; 3, H336	10-25%
1330-20-7	xylene	3, H226; 4, H332; 2, H315	10-25%
64742-95-6	Solvent naphtha (petroleum), light arom.	4, H332; 3, H335; 4, H227; 5, H313	½ 2,5%
80-62-6	methyl methacrylate	2, H225; 1, H317; 3, H335	½ 2,5%
26761-45-5	2,3-epoxypropyl neodecanoate	3, H331; H411; 2, H315; 5, H313	½ 2,5%
868-77-9	2-hydroxyethyl methacrylate	2, H315; 1, H317; 2, H401	½ 2,5%



: 19.09.2016

: 02.05.2015

: 635 OXIDE YELLOW

(4)



9

.
. :
.

(6)



: 19.09.2016

: 02.05.2015

: 635 OXIDE YELLOW

(5)

pH:		
		124 °C
		25 °C
		370 °C
		1,1 %
		7,5 %
	20 °C:	10,7
	20 °C:	1,108 /cm ³
VOC (EC)		39,2 %
		434,1 /
		60,1 %



: 19.09.2016

: 02.05.2015

: 635 OXIDE YELLOW

(6)

10

.
. -
. / , :
. , -
. :
. :

11

.
:

LD/LC50 (/),
:

1330-20-7 xylene

()	LD50	4300 / (rat)
()	LD50	2000 / (rabbit)

64742-95-6 Solvent naphtha (petroleum), light arom.

()	LD50	>6800 / (rat)
()	LD50	>3400 / (rab)
()	LC50/4	>10,2 / (rat)

. :
: :
: :
: :
: :
()

12

. :
: -
: -
: -
: -
: -

(8)
RU



: 19.09.2016

: 02.05.2015

: 635 OXIDE YELLOW

(8)

·	:	:
·	:	:
·	EMS: (): 30	F-E, S-E
·	Stowage Category	A
·	MARPOL73/78 (II)	
·	IBC Code ()	
·	/ :	
·	ADR (LQ) (EQ) 5L	: E1
·		: 30
·		: 1000
·		3
·		D/E
·	IMDG	
·	Limited quantities (LQ)	5L
·	Excepted quantities (EQ)	Code: E1
		Maximum net quantity per inner packaging: 30
		Maximum net quantity per outer packaging: 1000
·	UN "Model Regulation":	UN 1263 , 3, III

15

(GHS).

(10) RU



: 635 OXIDE YELLOW

(9)



xylene
Solvent naphtha (petroleum), light arom.
2,3-epoxypropyl neodecanoate

16

- H225
- H226
- H227
- H312
- H313
- H315
- H317
- H319
- H331
- H332

(11)
RU



: 19.09.2016

: 02.05.2015

: 635 OXIDE YELLOW

H335

H336

H401

H411

(10)

: Product safety department

: Ms. Topaljikian

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

2: Flammable liquids, Hazard Category 2

3: Flammable liquids, Hazard Category 3

4: Flammable liquids, Hazard Category 4

4: Acute toxicity, Hazard Category 4

5: Acute toxicity, Hazard Category 5

3: Acute toxicity, Hazard Category 3

2: Skin corrosion/irritation, Hazard Category 2

2: Serious eye damage/eye irritation, Hazard Category 2

1: Sensitisation - Skin, Hazard Category 1

3: Specific target organ toxicity - Single exposure, Hazard Category 3

2: Hazardous to the aquatic environment - Acute Hazard, Category 2

2: Hazardous to the aquatic environment - Chronic Hazard, Category 2