



: 19.09.2016

: 02.05.2015

1 / /

.
.
: **756 PURE MAROON**

: 756

.
.
General Paint Co. SAL
P.O. Box 7623
Beirut
LEBANON
www.generalpaint.biz

.
: Product safety department
: During normal opening times: (961) 9 925990 /1/2

2



3 H226



3 H336

5 H333

(GHS).



GHS02 GHS07

.
.
xylene
Solvent naphtha (petroleum), light arom.
ethylbenzene



: 19.09.2016

: 02.05.2015

: 756 PURE MAROON

Main table area containing chemical data, hazard symbols (e.g., PBT, vPvB), and hazard statements (H302, H332, H336, H315, H335, H313, H326, H332, H327, H335, H373, H332, H304).

3		
123-86-4	n-butyl acetate	25-50%
	3, H226; - 3, H336	
1330-20-7	xylene	2,5-10%
	3, H226; 4, H312; 4, H332; 2, H315	
64742-95-6	Solvent naphtha (petroleum), light arom.	2,5-10%
	4, H332; - 3, H335; 4, H227; 5, H313	
108-65-6	2-methoxy-1-methylethyl acetate	2,5-10%
	3, H226	
100-41-4	ethylbenzene	1/2 2,5%
	2, H225; 1, H304; - 2, H373; 4, H332	
		16.



: 19.09.2016

: 02.05.2015

: 756 PURE MAROON

(2)

4

·

· : ,

· : .

· : .

· : .

· - .

· - .

5

·

· CO₂,

· , :

· , .

· - .

· : .

6

· ,

· : / .

· : (, -).

· ,). 13.

· - 7. - 8. ()



: 756 PURE MAROON

- 13. () 3)

7

.

:

.

/

.

:

-

.

.

,

:

.

:

:

:

:

:

:

: 3

.

.

.

()

8

.

;

.

7.

:

.

123-86-4 n-butyl acetate

PDK	: 200 /m ³
	: 50 /m ³

1330-20-7 xylene

PDK	: 150 /m ³
	: 50 /m ³

108-65-6 2-methoxy-1-methylethyl acetate

PDK	: 10 /m ³
-----	----------------------

100-41-4 ethylbenzene

PDK	: 150 /m ³
	: 50 /m ³



: 19.09.2016

: 02.05.2015

: 756 PURE MAROON

(5)

.	:	.	.
.	:	.	.
.	pH:	.	.
.	:	/	.
.	:	/	.
.	:	120 °C	.
.	:	27 °C	.
.):	(,	.
.	:	315 °C	.
.	:	.	.
.	:	.	.
.	:	.	.
.	:	1,2 .%	.
.	:	7,5 .%	.
.	20 °C:	10,7	.
.	20 °C:	0,958 /cm ³	.
.	:	.	.
.	:	.	.
.	:	.	.
.	:	/	.
.):	(n- /	.
.	:	.	.
.	:	.	.
.	:	.	.
.	VOC (EC)	72,3 %	.
.	:	692,8 /	.
.	:	27,8 %	.



: 19.09.2016

: 02.05.2015

: 756 PURE MAROON

(6)

10

Fragmented text for section 10, including symbols like /, , and :

11

Fragmented text for section 11, including a colon symbol :

LD/LC50 (/),		
1330-20-7 xylene		
()	LD50	4300 / (rat)
()	LD50	2000 / (rabbit)
64742-95-6 Solvent naphtha (petroleum), light arom.		
()	LD50	>6800 / (rat)
()	LD50	>3400 / (rab)
()	LC50/4	>10,2 / (rat)

Fragmented text for section 11, including symbols like : and :

12

Fragmented text for section 12, including symbols like : and :

2 (-):

(8)



: 19.09.2016

: 02.05.2015

: 756 PURE MAROON

· **PBT (** ()⁷⁾
· **vPvB (**)
· **PBT:**
· **vPvB:**

13

· :
· :
· :

14

· **UN**
· **ADR, IMDG, IATA** UN1263

· **ADR** 1263
· **IMDG** PAINT
· **IATA** Paint

· **ADR, IMDG, IATA**



· 3
· 3

· **ADR, IMDG, IATA** III

· :
· :

· **EMS:** F-E,S-E



: 19.09.2016

: 02.05.2015

: 756 PURE MAROON

(8)

· **Stowage Category**

A

II

· **MARPOL73/78 (**

· **IBC Code (**

· **ADR**

(LQ)

(EQ)

5L

: E1

: 30

: 1000

3

D/E

· **IMDG**

· **Limited quantities (LQ)**

· **Excepted quantities (EQ)**

5L

Code: E1

Maximum net quantity per inner packaging: 30

Maximum net quantity per outer packaging: 1000

· **UN "Model Regulation":**

UN 1263

, 3, III

15

(GHS).



GHS02 GHS07

xylene

Solvent naphtha (petroleum), light arom.

ethylbenzene

(10)



: 756 PURE MAROON

9)

16

- H225
- H226
- H227
- H304
- H312
- H313
- H315
- H332
- H335
- H336
- H373

: Product safety department

: Ms. Topaljikian

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

11)

RU



: 19.09.2016

: 02.05.2015

: 756 PURE MAROON

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

2: Flammable liquids, Hazard Category 2

3: Flammable liquids, Hazard Category 3

4: Flammable liquids, Hazard Category 4

4: Acute toxicity, Hazard Category 4

5: Acute toxicity, Hazard Category 5

2: Skin corrosion/irritation, Hazard Category 2

- 3: Specific target organ toxicity - Single exposure, Hazard Category 3

- 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

1: Aspiration hazard, Hazard Category 1

(10)

RU