



: 19.09.2016

: 02.05.2015

1 / /

: **766 PEARL BLUE FINE**

: 766

General Paint Co. SAL
P.O. Box 7623
Beirut
LEBANON
www.generalpaint.biz

: Product safety department
: During normal opening times: (961) 9 925990 /1/2

2



3 H226



3 H336

5 H333

(GHS).



GHS02 GHS07

xylene
Solvent naphtha (petroleum), light arom.
ethylbenzene



: 766 PEARL BLUE FINE

(1)

/ / / / / /

/ / / / / /

():

/ / / / / /

PBT ()

vPvB ()

PBT:

vPvB:

3 /

123-86-4	n-butyl acetate	3, H226;	3, H336	50-100%
1330-20-7	xylene	3, H226; H312; 4, H332;	2, H315 4,	2,5-10%
64742-95-6	Solvent naphtha (petroleum), light arom.	 4, H332; 4, H227;	3, H335; 5, H313	2,5-10%
100-41-4	ethylbenzene	 2, H225; 1, H304;	2, H373; 4, H332	½ 2,5%

16.

4

(3)

RU





: 19.09.2016

: 02.05.2015

: 766 PEARL BLUE FINE

(4)

(Faint, illegible text describing safety and handling instructions)

9





: 766 PEARL BLUE FINE

		(5)
.		
/		
:		
		120 °C
.		
		27 °C
.		
		370 °C
.		
:		
.		
:		
		1,2 . %
		7,5 . %
20 °C:		10,7
20 °C:		0,984 /cm³
.		
.		
.		
/		
		(n- /
):		
:		
		72,5 %
VOC (EC)		713,9 /
		27,4 %

10



: 19.09.2016

: 02.05.2015

: 766 PEARL BLUE FINE

(6)

/ , :

,

-

:

11

:

:

LD/LC50 (/),

:

1330-20-7 xylene

()	LD50	4300 / (rat)
()	LD50	2000 / (rabbit)

64742-95-6 Solvent naphtha (petroleum), light arom.

()	LD50	>6800 / (rat)
()	LD50	>3400 / (rab)
()	LC50/4	>10,2 / (rat)

:

:

:

:

12

:

:

:

:

:

:

:

2 (-):

PBT ()

vPvB ()

PBT:

vPvB:



: 19.09.2016

: 02.05.2015

: 766 PEARL BLUE FINE

(7)

13

.
:
:
:
:

14

. **UN**
. **ADR, IMDG, IATA** UN1263

.
. **ADR** 1263
. **IMDG** PAINT
. **IATA** Paint

.
. **ADR, IMDG, IATA**



. 3
. 3

.
. **ADR, IMDG, IATA** III

. :
. :

. **EMS:** F-E,S-E

(9)



: 19.09.2016

: 02.05.2015

: 766 PEARL BLUE FINE

(8)

· **Stowage Category**

A

II

· **MARPOL73/78 (**

· **IBC Code (**

· **ADR**

(LQ)

5L

(EQ)

: E1

: 30

: 1000

3

D/E

· **IMDG**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30

Maximum net quantity per outer packaging: 1000

· **UN "Model Regulation":**

UN 1263

, 3, III

15

(GHS).



GHS02 GHS07

xylene
Solvent naphtha (petroleum), light arom.
ethylbenzene

(10)



: 19.09.2016

: 02.05.2015

: 766 PEARL BLUE FINE

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

2: Flammable liquids, Hazard Category 2

3: Flammable liquids, Hazard Category 3

4: Flammable liquids, Hazard Category 4

4: Acute toxicity, Hazard Category 4

5: Acute toxicity, Hazard Category 5

2: Skin corrosion/irritation, Hazard Category 2

- 3: Specific target organ toxicity - Single exposure, Hazard Category 3

- 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

1: Aspiration hazard, Hazard Category 1

(10)

RU