



: 19.09.2016

: 02.05.2015

1

: **872 XIRALLIC WHITE**

: 872

General Paint Co. SAL
P.O. Box 7623
Beirut
LEBANON
www.generalpaint.biz

: Product safety department
: During normal opening times: (961) 9 925990 /1/2

2



3 H226



3 H336

5 H333

(GHS).



GHS02 GHS07

xylene
Solvent naphtha (petroleum), light arom.
ethylbenzene



: 872 XIRALLIC WHITE

(1)

/ / / / /

/ / / / / ():

/ / / / /

vPvB (PBT ())

PBT:

vPvB:

3

123-86-4	<i>n</i> -butyl acetate	3, H226; !	3, H336	50-100%
1330-20-7	xylene	3, H226; ! H312; 4, H332;	2, H315 4,	2,5-10%
64742-95-6	Solvent naphtha (petroleum), light arom.	4, H332; 4, H227;	3, H335; 5, H313	2,5-10%
108-65-6	2-methoxy-1-methylethyl acetate	3, H226		2,5-10%
100-41-4	ethylbenzene	2, H225; ! 1, H304; !	2, H373; 4, H332	½ 2,5%

16.

RU

3)



1907/2006/EC,

31

: 19.09.2016

: 02.05.2015

: 872 XIRALLIC WHITE

() 2)

4

.
. :
. :
. :
. :
. :
. :
. -
. -

5

.
CO₂,
. ,
. ,
. :
. -

6

. ,
. :
. /
. :
. , (, -
. ,) . 13.
. - 7.

()

.
. :
. /
. :
. , (, -
. ,) . 13.

- 7.
. - 8.
(



1907/2006/EC, 31

: 19.09.2016

: 02.05.2015

: 872 XIRALLIC WHITE

13. (3)

7

Fragmented text with various symbols and a colon followed by '3'.

8

Fragmented text including a semicolon and the number '7'.

Fragmented text.

123-86-4 n-butyl acetate

PDK : 200 /m³
: 50 /m³

1330-20-7 xylene

PDK : 150 /m³
: 50 /m³

108-65-6 2-methoxy-1-methylethyl acetate

PDK : 10 /m³

100-41-4 ethylbenzene

PDK : 150 /m³
: 50 /m³



: 19.09.2016

: 02.05.2015

: 872 XIRALLIC WHITE

(5)

·	:	
·	:	
·	pH:	
·	:	/
·	:	/
·	:	120 °C
·	:	27 °C
·):	(,
·	:	370 °C
·	:	
·	:	
·	:	/
·	:	
·	:	1,2 .%
·	:	7,5 .%
·	20 °C:	10,7
·	20 °C:	0,962 /cm ³
·	:	
·	:	
·	:	
·	:	/
·):	(n- /
·	:	
·	:	
·	:	
·	VOC (EC)	74,3 %
·	:	714,5 /
·	:	25,7 %



: 19.09.2016

: 02.05.2015

: 872 XIRALLIC WHITE

(6)

10

...
... / , :
... , -
... :
...

11

...
... :

LD/LC50 (/),
:

1330-20-7 xylene

()	LD50	4300 / (rat)
()	LD50	2000 / (rabbit)

64742-95-6 Solvent naphtha (petroleum), light arom.

()	LD50	>6800 / (rat)
()	LD50	>3400 / (rab)
()	LC50/4	>10,2 / (rat)

...
... :
... :
... :

12

...
... :
... -
... :
... -
... :
... :

2 (-):

(8)



: 19.09.2016

: 02.05.2015

: 872 XIRALLIC WHITE

· **PBT (** ()⁷⁾
· **vPvB (**)
· **PBT:**
· **vPvB:**

13

· :
· :
· :
· :

14

· **UN**
· **ADR, IMDG, IATA** UN1263

· **ADR** 1263
· **IMDG** PAINT
· **IATA** Paint

· **ADR, IMDG, IATA**



· 3
· 3

· **ADR, IMDG, IATA** III

· :
· :

· :

· **EMS:** (): 86
· **F-E,S-E**



: 19.09.2016

: 02.05.2015

: 872 XIRALLIC WHITE

(8)

· **Stowage Category**

A

·

II

MARPOL73/78 (

)

IBC Code (

)

·

/

:

· **ADR**

·

(LQ)

5L

·

(EQ)

: E1

: 30

: 1000

·

3

·

D/E

· **IMDG**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30

Maximum net quantity per outer packaging: 1000

· **UN "Model Regulation":**

UN 1263

, 3, III

15

·

·

·

(GHS).



GHS02 GHS07

·

·

xylene

Solvent naphtha (petroleum), light arom.

ethylbenzene

(

10)

RU



: 10/11

1907/2006/EC, 31

: 19.09.2016

: 02.05.2015

: 872 XIRALLIC WHITE

<p>(9)</p> <p>:</p> <p>:</p> <p>,</p> <p>,</p> <p>/ / / / / / / / /</p> <p>():</p> <p>/ / / / /</p> <p>/ / / / / / / /</p> <p>:</p>

16 :

- H225
- H226
- H227
- H304
- H312
- H313
- H315
- H332
- H335
- H336
- H373

: Product safety department

: Ms. Topaljikian

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)



: 19.09.2016

: 02.05.2015

: 872 XIRALLIC WHITE

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

2: Flammable liquids, Hazard Category 2

3: Flammable liquids, Hazard Category 3

4: Flammable liquids, Hazard Category 4

4: Acute toxicity, Hazard Category 4

5: Acute toxicity, Hazard Category 5

2: Skin corrosion/irritation, Hazard Category 2

- 3: Specific target organ toxicity - Single exposure, Hazard Category 3

- 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

1: Aspiration hazard, Hazard Category 1

(10)

RU