



: 19.09.2016

: 02.05.2015

1

.
.
: **645 OXIDE RED**
: 645

.
.
General Paint Co. SAL
P.O. Box 7623
Beirut
LEBANON
www.generalpaint.biz

: Product safety department
: During normal opening times: (961) 9 925990 /1/2

2



3 H226



3 H336

5 H333

(GHS).



GHS02 GHS07

xylene
Solvent naphtha (petroleum), light arom.



: 19.09.2016

: 02.05.2015

: 645 OXIDE RED

()

/ / / / / / / / / /

():

/ / / / / / / / / /

PBT ()

vPvB ()

PBT:

vPvB:

3 /

123-86-4	n-butyl acetate	3, H226; !	3, H336	10-25%
13463-67-7	titanium dioxide	5, H333		10-25%
108-65-6	2-methoxy-1-methylethyl acetate	3, H226		2,5-10%
1330-20-7	xylene	3, H226; !	4, H312; 4, H332; 2, H315	2,5-10%
64742-95-6	Solvent naphtha (petroleum), light arom.	4, H332; 4, H227;	3, H335; 5, H313	2,5-10%

16.

4

()

3)

RU



: 19.09.2016

: 02.05.2015

: 645 OXIDE RED

(3)

:

:

:

:

:

:

: 3

()

8

/

; . 7. :

:

123-86-4 n-butyl acetate

PDK	: 200 /m ³
	: 50 /m ³
/	

108-65-6 2-methoxy-1-methylethyl acetate

PDK	: 10 /m ³
/	

1330-20-7 xylene

PDK	: 150 /m ³
	: 50 /m ³
/	

:

:

:

:

:

:

:

:

:

1907/2006/EC,

31

: 19.09.2016

: 02.05.2015

: 645 OXIDE RED

9

pH:

124 °C

25 °C

6)

-RU



: 19.09.2016

: 02.05.2015

: 645 OXIDE RED

(6)

11

.

LD/LC50 (/),

64742-95-6 Solvent naphtha (petroleum), light arom.

()	LD50	>6800 / (rat)
()	LD50	>3400 / (rab)
()	LC50/4	>10,2 / (rat)

.

12

.

.

.

.

3 (-):

,

PBT ()

vPvB ()

PBT:

vPvB:

13

.

(8)



: 19.09.2016

: 02.05.2015

: 645 OXIDE RED

(7)

14

· UN
· ADR, IMDG, IATA UN1263

· ADR 1263
· IMDG PAINT
· IATA Paint

· ADR, IMDG, IATA



3
3

· ADR, IMDG, IATA III

· EMS: F-E, S-E
· Stowage Category A

MARPOL73/78 (II)
IBC Code ()

· ADR
(LQ) (EQ) 5L : E1

: 30



: 19.09.2016

: 02.05.2015

: 645 OXIDE RED

(8)

·		: 1000
·	3	
·	D/E	
<hr/>		
· IMDG		
· Limited quantities (LQ)	5L	
· Excepted quantities (EQ)	Code: E1	
	Maximum net quantity per inner packaging: 30	
	Maximum net quantity per outer packaging: 1000	
<hr/>		
· UN "Model Regulation":	UN 1263	, 3, III

15



(GHS).

xylene
 Solvent naphtha (petroleum), light arom.



: 19.09.2016

: 02.05.2015

: 645 OXIDE RED

(9)

16

- H226
- H227
- H312
- H313
- H315
- H332
- H333
- H335
- H336

: Product safety department

: Ms. Topaljikian

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

3: Flammable liquids, Hazard Category 3

4: Flammable liquids, Hazard Category 4

4: Acute toxicity, Hazard Category 4

5: Acute toxicity, Hazard Category 5

2: Skin corrosion/irritation, Hazard Category 2

3: Specific target organ toxicity - Single exposure, Hazard Category 3