



: 19.09.2016

: 02.05.2015

1

: 739 BRILLIANT YELLOW

: 739

General Paint Co. SAL
P.O. Box 7623
Beirut
LEBANON
www.generalpaint.biz

: Product safety department
: During normal opening times: (961) 9 925990 /1/2

2



3 H226



2 H315
3 H336
5 H333

(GHS).



GHS02 GHS07

xylene
Solvent naphtha (petroleum), light arom.



: 19.09.2016

: 02.05.2015

: 739 BRILLIANT YELLOW

() 1)

vPvB (
PBT:
vPvB:

PBT ()

3

123-86-4	<i>n</i> -butyl acetate	3, H226; 3, H336	25-50%
1330-20-7	xylene	3, H226; 4, H312; 4, H332; 2, H315	10-25%
108-65-6	2-methoxy-1-methylethyl acetate	3, H226	2,5-10%
64742-95-6	Solvent naphtha (petroleum), light arom.	4, H332; 4, H227; 3, H335; 5, H313	2,5-10%

16.

4



: 19.09.2016

: 02.05.2015

: 739 BRILLIANT YELLOW

(2)

.

:

()

.

:

,

.

:

.

:

:

:

.

,

,

.

-

.

.

-

.

5

.

.

CO2,

.

,

.

,

-

.

.

:

-

.

6 ()

.

,

.

:

/

:

.

(, , -

, ,).

13.

.

-

7.

-

8.

-

13.



: 739 BRILLIANT YELLOW

(3)

7

Fragment of safety data sheet text, mostly illegible.

8

Fragment of safety data sheet text, mostly illegible.

Fragment of safety data sheet text, mostly illegible.

123-86-4 n-butyl acetate

PDK : 200 /m³
: 50 /m³

1330-20-7 xylene

PDK : 150 /m³
: 50 /m³

108-65-6 2-methoxy-1-methylethyl acetate


PDK : 10 /m³

Fragment of safety data sheet text, mostly illegible.

: 739 BRILLIANT YELLOW



9



pH:



: 19.09.2016

: 02.05.2015

: 739 BRILLIANT YELLOW

		(5)
.		
/		
:		
/		
		120 °C
		27 °C
): (,		
		315 °C
:		
:		
:		
/		
		1,1 . %
		7,5 . %
20 °C:		10,7
20 °C:		0,942 /cm³
.		
.		
.		
/		
		(n- /
):		
:		
:		
:		
VOC (EC)		77,2 %
		727,3 /
		22,9 %

10



: 19.09.2016

: 02.05.2015

: 739 BRILLIANT YELLOW

(6)

.

/ , :

.

,

-

:

11

LD/LC50 (/),		
1330-20-7 xylene		
()	LD50	4300 / (rat)
()	LD50	2000 / (rabbit)
64742-95-6 Solvent naphtha (petroleum), light arom.		
()	LD50	>6800 / (rat)
()	LD50	>3400 / (rab)
()	LC50/4	>10,2 / (rat)

12

.

:

-

.

:

-

:

2 (-):

,

(



: 19.09.2016

: 02.05.2015

: 739 BRILLIANT YELLOW

· PBT ()

· vPvB ()

· PBT: ()

· vPvB: ()

13

· :

· :

14

· **UN**

· **ADR, IMDG, IATA** UN1263

· **ADR** 1263

· **IMDG** PAINT

· **IATA** Paint

· **ADR, IMDG, IATA**



· 3

· 3

· **ADR, IMDG, IATA** III

· :

· :

· :

· **EMS:** F-E,S-E



: 19.09.2016

: 02.05.2015

: 739 BRILLIANT YELLOW

(8)

· **Stowage Category**

A

· **MARPOL73/78 (**

II

· **IBC Code (**

· **ADR**

(LQ)

5L

(EQ)

: E1

: 30

: 1000

3

D/E

· **IMDG**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30

Maximum net quantity per outer packaging: 1000

· **UN "Model Regulation":**

UN 1263

, 3, III

15

(GHS).



GHS02 GHS07

xylene

Solvent naphtha (petroleum), light arom.

(10)



: 19.09.2016

: 02.05.2015

: 739 BRILLIANT YELLOW

(9)

16

- H226
- H227
- H312
- H313
- H315
- H332
- H335
- H336

: Product safety department

: Ms. Topaljikian

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- 3: Flammable liquids, Hazard Category 3
- 4: Flammable liquids, Hazard Category 4

(11)

RU



: 11/11

1907/2006/EC, 31

: 19.09.2016

: 02.05.2015

: 739 BRILLIANT YELLOW

- 4: Acute toxicity, Hazard Category 4
- 5: Acute toxicity, Hazard Category 5
- 2: Skin corrosion/irritation, Hazard Category 2
- 3: Specific target organ toxicity - Single exposure, Hazard Category 3

(10)

RU