



: 19.09.2016

: 02.05.2015

1

: 795 METALLIC BASE MEDIUM FINE

: 795

General Paint Co. SAL
P.O. Box 7623
Beirut
LEBANON
www.generalpaint.biz

: Product safety department
: During normal opening times: (961) 9 925990 /1/2

2



3 H226



2 H315

3 H336

5 H333

(GHS).



GHS02



GHS07

xylene
Solvent naphtha (petroleum), light arom.
ethylbenzene



: 19.09.2016

: 02.05.2015

: 795 METALLIC BASE MEDIUM FINE

(1)

/ / / / / /

():

().

/ / / / /

PBT ()

vPvB ()

PBT:

vPvB:

3 /

123-86-4	<i>n</i> -butyl acetate	3, H226; 3, H336	50-100%
1330-20-7	xylene	3, H226; 4, H332; 2, H315	10-25%
64742-95-6	Solvent naphtha (petroleum), light arom.	4, H332; 4, H227; 3, H335; 5, H313	2,5-10%
7429-90-5	aluminium powder (pyrophoric)	1, H250; 2, H261	2,5-10%
108-65-6	2-methoxy-1-methylethyl acetate	3, H226	½ 2,5%
100-41-4	ethylbenzene	2, H225; 1, H304; 2, H373; 4, H332	½ 2,5%

3)

RU



1907/2006/EC, 31

: 19.09.2016

: 02.05.2015

: 795 METALLIC BASE MEDIUM FINE

. : (.²⁾
16.

4

.
.
.
.
.
.
.
.
.
.
.

5

.
.
CO2,
.
.
.
.
.

6 ()

.
.
.
.
.
.
13.
.
4)
RU



: 19.09.2016

: 02.05.2015

: 795 METALLIC BASE MEDIUM FINE

(3)

7.

8.

13.

7

7.

8.

13.

14.

15.

16.

17.

18.

19.

20.

21.

22.

23.

24.

25.

26.

27.

28.

29.

30.

31.

32.

33.

34.

35.

36.

37.

38.

39.

40.

41.

42.

43.

44.

45.

46.

47.

48.

49.

50.

51.

52.

53.

54.

55.

56.

57.

58.

59.

60.

61.

62.

63.

64.

65.

66.

67.

68.

69.

70.

71.

72.

73.

74.

75.

76.

77.

78.

79.

80.

81.

82.

83.

84.

85.

86.

87.

88.

89.

90.

91.

92.

93.

94.

95.

96.

97.

98.

99.

100.

8

7.

123-86-4 n-butyl acetate	
PDK	: 200 /m ³ : 50 /m ³
1330-20-7 xylene	
PDK	: 150 /m ³ : 50 /m ³
108-65-6 2-methoxy-1-methylethyl acetate	
PDK	: 10 /m ³



: 19.09.2016

: 02.05.2015

: 795 METALLIC BASE MEDIUM FINE

100-41-4 ethylbenzene

(4)

PDK	: 150 /m ³
/	: 50 /m ³





: 19.09.2016

: 02.05.2015

: 795 METALLIC BASE MEDIUM FINE

(6)

): (n- /	
:	
:	
VOC (EC)	: 75,8 % 719,9 /
:	24,2 %

10

·

·

· / , :

·

· , - :

·

11

·

· :

· **LD/LC50** (/),

·

1330-20-7 xylene		
()	LD50	4300 / (rat)
()	LD50	2000 / (rabbit)
64742-95-6 Solvent naphtha (petroleum), light arom.		
()	LD50	>6800 / (rat)
()	LD50	>3400 / (rab)
()	LC50/4	>10,2 / (rat)

·

· :

·

·



: 19.09.2016

: 02.05.2015

: 795 METALLIC BASE MEDIUM FINE

(7)

()

12

·

· :

· -

· :

· -

· :

· -

· :

· PBT ()

vPvB ()

· PBT:

· vPvB:

13

·

· :

·

· :

·

14

· UN	
· ADR, IMDG, IATA	UN1263
· ADR	1263
· IMDG	PAINT
· IATA	Paint

(9)



: 795 METALLIC BASE MEDIUM FINE

(8)

· **ADR, IMDG, IATA**



3
3

· **ADR, IMDG, IATA**

III

· **EMS:**
· **Stowage Category**

F-E, S-E
A

· **MARPOL73/78 (**

II

IBC Code (

· **ADR**

(LQ)

5L

(EQ)

: E1

: 30

: 1000

3

D/E

· **IMDG**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30

Maximum net quantity per outer packaging: 1000

· **UN "Model Regulation":**

UN 1263

, 3, III



: 795 METALLIC BASE MEDIUM FINE

(9)

15



GHS02 GHS07

(GHS).

xylene
Solvent naphtha (petroleum), light arom.
ethylbenzene

16

H225
H226
H227



: 19.09.2016

: 02.05.2015

: 795 METALLIC BASE MEDIUM FINE

- H250
- H261
- H304
- H312
- H313
- H315
- H332
- H335
- H336
- H373

(10)

: Product safety department

: Ms. Topaljikian

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

2: Flammable liquids, Hazard Category 2

3: Flammable liquids, Hazard Category 3

4: Flammable liquids, Hazard Category 4

1: Pyrophoric Solids, Hazard Category 1

2: Substances and Mixtures which, in contact with water, emit flammable gases, Hazard

Category 2

4: Acute toxicity, Hazard Category 4

5: Acute toxicity, Hazard Category 5

2: Skin corrosion/irritation, Hazard Category 2

3: Specific target organ toxicity - Single exposure, Hazard Category 3

2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

1: Aspiration hazard, Hazard Category 1